


IRB 341

Next Generation High Speed Drill















TECHNICAL SPECIFICATION

IRB-341 is intended for construction, quarrying and open pit mining. The main features are:

- Pneumatic-powered traction motors with gear and chain drive.
- Pneumatic-operated hydraulic power pack for hydraulic cylinders.
- Pneumatic operated feed system suitable for 10 feet rod handling capacity.
- Single grouser with heavy duty shoe that provide better traction performance and drawbar force as well as easy movement in critical terrain areas of tramining.
- More sturdy box type track frame.

- Heavy duty track roller with oil filled, no regular greasing is required and Easy removal.
- Bigger size sprocket for more machine traveling speed. Sidemounted tramming and positioning controls.
- · Enormous ground clearance.
- Pneumatic operated 60 liter dust suppression system.
- · Heavy duty fabricated boom system.
- · Hydraulic track oscillation system.
- · Drilling depth up to 15 Meters.

HOLE RANGE

Pipe Size	No of Rod	Rod Length	Recommended Hole Range	
75mm (3")	3 Rods	3048 mm (10 Ft.)	102 –115 mm (4" - 4.5")	

SPECIFICATION:

Carrier

Tramming Speed, Max	3.1 km/h
Traction Force, Max	17 kN
Track Oscillation	± 10°
Ground Clearance	. 277 mm
Hill Climbing Ability 30 deg Max. (w/o Compressor)	

Volumes

Hydraulic Oil	30 L
Hydraulic System (Total)	35 L
Traction Gear	2 L
Lubrication Tank	8 L

Feed System

Pneumatic driven chain feed :	
Feed Extension	750 mm
Feed Rate, max	0.3 m/s.
Feed Force, max (pull up)	21 kN
Feed Force (pull down)	21 kN
Steel feed length	4394 mm

Machine Weight

Travel length

Machine Weight (Approx)	3150 kg
Machine Weight (Approx)	3130 kg

Rotary Head

Rotary Head	Connection Thread	Max RPM	Max Torque, Drilling	Suitable for DTH Hammer
RH	2 3/8" API	0-100	2500 Nm	R0CK40/42/44

Specification is subject to change without prior notice.

...... 3694 mm

NAKODA MACHINERY PVT. LTD.

Corporate Office: 139, 1st Floor, Patil Plaza, Mitra Mandal Chowk, Pune 411009 (Maharashtra, INDIA)

Helpline: 1800 233 6388

+91 020 2444 9600, 4120 3772

sales@irt.co.in, Info@irt.co.in

www.indusrocktool.co.in

@IndusRockTool **in** indus-rock-tool **f** Indusrocktool.official



Authorised Dealer